


# ACOUSTIC HYBRID MOUNT

Series: **STRIB CAB**



- Eradicates and attenuates noise and vibration above 6Hz.
- Tested to acoustic standard ISO 10846-1.
- No screws required.
- Easy to position and install.
- Locking configuration holds structure in place in event of fire.
- Optimal load: 3kg to 120kg per mount.
- Suited for false acoustic ceilings using galvanized steel profiles such as STIL PRIM 100.

**MATERIAL**

- Polymer Body: Kraiburg TPE
- Metal structure: Galvanised steel Dx54d + Z140
- Bowl shaped leveller: Galvanised steel Dx54d + Z140

Part Number	Colour	Thread Size	Weight Range per mount (Kg)	Break Test	TPE Properties
STRIB CAB 20G	Grey	M6, M8	3 ~ 20	-	-
STRIB CAB 45V	Green	M6, M8	15 ~ 45	<a href="#">PDF</a>	<a href="#">PDF</a>
STRIB CAB 75A	Blue	M6, M8	30 ~ 75	<a href="#">PDF</a>	<a href="#">PDF</a>
STRIB CAB 120R	Red	M6, M8	60 ~ 120	<a href="#">PDF</a>	<a href="#">PDF</a>

**Resonance Point:** 3-7 Hz

