

CONDUCTIVE TAPE

series: CCT



- Thin and flexible foil tape backed by conductive adhesive.
- Highly conductive adhesive provides high shielding effectiveness.
- Easy to cut for custom configurations.
- ROHS compliant.

Material


Base material: CCT-C: Copper foil, CCT-A: Aluminium foil

Adhesive layer: Conductive adhesive

Standard roll length: 20m

Part Number	Width (mm)	Thickness (mm)	Adhesive strength	Resistivity
CCT-8-C	8	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-10-C	10	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-13-C	13	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-20-C	20	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-25-C	25	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-50-C	50	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-100-C	100	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-600-C	600	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-250-C1*	250	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-A4-C1*	A4	0.075	9.4N/25mm	0.004 Ω/inch ²
CCT-6-A	6	0.09	8.6N/25mm	0.008 Ω/inch ²
CCT-8-A	8	0.09	8.6N/25mm	0.008 Ω/inch ²
CCT-15-A	15	0.09	8.6N/25mm	0.008 Ω/inch ²
CCT-20-A	20	0.09	8.6N/25mm	0.008 Ω/inch ²
CCT-25-A	25	0.09	8.6N/25mm	0.008 Ω/inch ²
CCT-A4-A1*	A4	0.09	8.6N/25mm	0.008 Ω/inch ²

* Sheet format



For engineering drawings, 3D files or additional test data please contact our [sales team](#).

ANNOTATION

All specifications shown herein are typical values and are not guaranteed. It is recommended to test in the application for suitability.