

## COMPONENT SPECIFICATION

Name	Ferrite Chip EMI Suppressors <b>MFB-160808-0060PQ</b>	COMPOSITE SPECIFICATION		1 / 2
		SPEC#	MFB-160808-0060PQ	

1. SCOPE

This specification applies to the **MFB-160808** series Ferrite Chip EMI suppressors.

2. STANDARD ATMOSPHERIC CONDITIONS

Unless otherwise specified the standard range of atmospheric conditions for making measurements and tests is as follows:

Ambient temperature :  $20 \pm 15^\circ\text{C}$

Relative humidity : 30~70%

If there may be any doubt on the results, measurements shall be made within the following limits :

Ambient temperature :  $25 \pm 5^\circ\text{C}$


Relative humidity : 30~70%

3. RATINGS

IMPEDANCE ( $\Omega$ ) AT100 MHz 500mV	DC RESISTANCE ( $\Omega$ ) Max	※ RATED CURRENT (mA) Max
$60 \pm 25\%$	0.04	3000

※The maximum rated current : the DC current value having temperature increased  $40^\circ\text{C}$  after thru DC current 2 hours at ambient temperature.

4. DIMENSION



OPERATING TEMP. RANGE :  $-55^\circ\text{C} \sim +125^\circ\text{C}$

STORAGE TEMP. RANGE :  $-10^\circ\text{C} \sim +40^\circ\text{C}$

L	W	T	A
$1.6 \pm 0.15$	$0.8 \pm 0.15$	$0.8 \pm 0.15$	0.2~0.6
<small>(0.063±0.006)</small>	<small>(0.031±0.006)</small>	<small>(0.031±0.006)</small>	<small>(0.008~0.024)</small>

5. The place of origin :

Taiwan

HISTORY	DATE	REVISION	SIGN.	SIGN.
PLANNED BY	CHECKED BY	APPROVED BY		

# COMPONENT SPECIFICATION

Name	Ferrite Chip EMI Suppressors	COMPOSITE SPECIFICATION		2 / 2
	MFB-160808-0060PQ	SPEC#	MFB-160808-0060PQ	

